







东莞市地安电子科技有限公司
DONGGUAN CITY DIERAN ELECTRONICS CO.,LTD

REVISION RECORD				
REV.	DESCRIPTION	ECN NO.	APPROVED	DATE

6.00*N-1 (N为位数)



项目/参数/认证



额定电压 (Rated Voltage) [V]

250

250

250

250

额定电流 (Rated Current) [A]

16

17.5

17.5

10

额定线经平方 (Wire Range mm²)

0.2-1.5

0.2-1.5

0.2-1.5

0.2-1.5

额定线经线号 (Wire Range AWG)

24-16

24-16

24-16

24-16

冲击电压 Impulse withstand voltage

4 (KV)

剥线长度 (Stripping Length) [mm]

8-9 (mm)

绝缘材料 (Insulation Material)

PA66 UL94V-0

导体材料 (Contactor Material)

黄铜 (brass)

导体表面镀层 (Contactive Coating)

镀锡 (Dumb tin)

间距 (Pitch) [mm]

6.0

级数 (Poles) [P]

2-32P

工作温度 (Operating temperatur) [°C]

-40°C ~ +105°C

焊锡温度 (Soldering temperature) [°C]

250°C / 5S

linear dimension (Tolerances Standard GB/T 14486-2008)

— □ ⊥

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to		over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	名称/TITLE	版本/REV	V0
东莞市地安电子科技有限公司							DA803V-6.0 直针		