




项目/参数/认证		
额定电压(Rated Voltage) [V]	450	750
额定电流(Rated Current) [A]	41	41
额定线经平方(Wire Range) [mm²]	0.34-6.0	0.2-6.0
额定线经线号(Wire Range) [AWG]	22-10	24-10
冲击电压 (Impulse withstand voltage)	5 (KV)	
剥线长度(Stripping Length) [mm]	6-7 (mm)	
螺丝/扭矩(Screw Torque Max)	M3.0/0.5 (N.m)	
绝缘材料(Insulation Material)	PA66 UL94V-0	
导体材料(Contactor Material)	红铜(Red copper)	
导体表面镀层(Contactive Coating)	镀锡 (Dumb tin)	
间距(Pitch) [mm]	7.62	
级数(Poles) [P]	2-24P	
工作温度(Operating temperatur) [°C]	-40°C ~+105°C	
焊锡温度(Soldering temperature) [°C]	250°C/5S	



linear dimension (Tolerances Standard GB/T 14486-2008)								—	$\square$	$\perp$
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/ REV	VO
东莞市地安电子科技有限公司								
						名称/ TITLE	DA168-7.62 无底座 中脚/正脚/反脚	