




东莞市地安电子科技有限公司
DONGGUAN CITY DIERAN ELECTRONICS CO.,LTD

REVISION RECORD

REV.	DESCRIPTION	ECN NO.	APPROVED	DATE



项目/参数/认证	
额定电压 (Rated Voltage) [V]	600
额定电流 (Rated Current) [A]	100
额定线经平方 (Wire Range) [mm ²]	38 (Max)
额定线经线号 (Wire Range) [AWG]	2 (Max)
冲击电压 (Impulse withstand voltage)	6 (KV)
螺丝/扭矩 (Screw Torque Max)	M6. 0/2. 5 (N. m)
绝缘材料 (Insulation Material)	PBT
导体材料 (Contactor Material)	铜 (Copper)
导体表面镀层 (Contactive Coating)	镀镍 (Nickel Plating)
间距 (Pitch) [mm]	21. 0
级数 (Poles) [P]	2-24P
工作温度 (Operating temperatur) [°C]	-40°C ~+105°C

linear dimension (Tolerances Standard GB/T 14486-2008)								—	∥	⊥
variable range	to	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to	over 10 to 100	over 100 to	
tolerance	±0. 20	±0. 30	±0. 50	±0. 70	±1. 00	±1. 30	±1. 60	0. 10	0. 30	0. 60

单位/UNITS	mm	尺寸/SIZE	A4	比例/SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本/REV	V0
东莞市地安电子科技有限公司						名称/TITLE	PG38-21. 0	